

TECHNICAL SPECIFICATIONS

GNSS Feature	Specification	
GNSS Signal ^①	Channels	1408
	GPS	L1C(A) / L1C / L2P(Y) / L2C / L5
	BDS	B1I / B2I / B3I / B1C / B2a / B2b
	GLONASS	L1 / L2 / L3
	Galileo	E1 / E5a / E5b / E6
	QZSS	L1 / L2 / L5 / L6*
	NavIC	L5
	SBAS	L1 / L2 / L5
	PPP	B2b-PPP / Galileo E6-HAS
Positioning Performance ^②	High-precision static GNSS Surveying	Horizontal: 2.5mm + 0.1ppm RMS Vertical: 3.5mm + 0.4ppm RMS
	Static and Fast Static	Horizontal: 2.5mm + 0.5ppm RMS Vertical: 5mm + 0.5ppm RMS
	Post Processing Kinematic (PPK / Stop & Go)	Horizontal: 8mm + 1ppm RMS Vertical: 15mm + 1ppm RMS
		Initialization time: Typically 10 min for base and 5 min for rover
	PPP	Initialization reliability: Typically>99.9%
		Horizontal: 10cm Vertical: 20cm
	Code Differential GNSS Positioning	Horizontal: ±0.25m+1ppm RMS Vertical: ±0.5m+1ppm RMS
	Real Time Kinematic (RTK)	SBAS: 0.5m(H), 0.85m(V)
		Horizontal: 8mm+1ppm RMS Vertical: 15mm+1ppm RMS
	Positioning rate	Initialization time: Typically <10s Initialization reliability: Typically > 99.9%
Communication	Communication	Bluetooth: BT 5.2, 2.4GHz
	Internal UHF Radio	Wi-Fi: frequency 2.4GHz, Supports 802.11 b/g/n Frequency: 410-470MHz Channel: 116 (16 scalable) Transmitting power: 0.5W / 1W / 2W adjustable Supports multi-communication protocols: HI-TARGET, TRIMTALK450S, TRIMMARK III, TRANSEOT, SATEL-3AS, etc.
Physical	Internal battery ^④	Internal 7.2V / 6900mAh lithium-ion rechargeable battery RTK Rover (UHF/Cellular): up to 24 hours*
	External power	Charging: using standard smartphone chargers or external power banks. Weight: ≤0.8kg (includes battery) Dimensions (W×H): 132mm×67mm Data storage: 16GB ROM internal storage
Control Panel	LED Lamp	Satellite, Signal, Power
	Physical button	1
Environment	Water / Dustproof	IP68
	Free fall	Designed to survive a 2m natural fall onto concrete
	Humidity	100%, condensing
	Operation temperature	-45℃ to +75℃
I / O Interface	Storage temperature	-55℃ to +85℃
	1 × USB port, Type C	
Data Formats	1 × SMA antenna connector	
	Output rate	1Hz-20Hz.
	Static data format	GNS, Rinex
	Network model	VRS, FKP, MAC; supports NTRIP protocol
	Real Time Kinematic (RTK)	RTCM2.X, RTCM3.X, CMR
	Navigation outputs ASCII	NMEA-0183

***Description and Specifications are subject to change without notice.**

1.QZSS L6 can be provided by firmware upgrade.

2.The measurement accuracy, precision, reliability and initialization time depend on various factors, including tilt angle, number of satellites, geometric distribution, observation time, atmospheric conditions and multi-path validation, etc. The data are derived under normal conditions.

3.Accuracies are dependent on GNSS satellite availability. Hi-Fix Positioning ends after 5 minutes without differential data.Hi-Fix is not available in all regions, check with your local sales representative for more information.

4.Irregular operations such as rapid rotation and high-intensity vibration may affect the inertial navigation accuracy.

5.The battery operating time is related to the operating environment, operating temperature and battery life.

AUTHORIZED DISTRIBUTION PARTNER

24S112

V200

GNSS RTK System



IP68



V200

Good things come in small packages

V200 GNSS RTK Receiver brings superior performance and high efficiency to support your fieldwork with reliable solutions. Its deployment of the advanced RTK engine and new-generation IMU guarantees a 25% performance improvement even in the most demanding environments. Thus you can count on Hi-Target V200 for better productivity.

Key Features

Advanced RTK Engine

Full-Constellation Tracking

Web UI

Built-in Radio

NFC

Compatibility with third-party software


• More Portability

Equipped with an ultra-light EPP material instrument case of a high anti-strong impact, shock and impact resistance and a centering rod that can be contracted to 1.25 m, making it durable and portable in the fieldwork.




• Greater Flexibility

It can bring accurate and reliable results and boost efficient fieldwork with self-developed built-in IMU and core algorithm.




• Higher Accuracy and Precision

Equipped with the High-Performance Patch Antenna, enhances the low elevation angle tracking capabilities and keeps it maintaining a high gain for higher elevation satellites while tracking low-elevation satellites.



• More Stability

Hi-Target **Hi-Fix** enables continuous connectivity and quality results even if you lose the signal while using the RTK base station or VRS network under extreme circumstances.




Hi-Survey


Survey Data Collection Software



AR stakeout to guide directions with the intelligent voice and compass.



Optimized tilt survey and able to complete the initialization by shaking the receiver for 2-5s and maintain a high-precision measurement status for a long time.



Users can view the number of the tracking satellites, PDOP, Elevation Mask, the current satellite constellations and other information in the sky plot interface.



Advanced CAD data management, supporting importing files of DXF, DWG format, and achieving data stakeout by the object snap functions of INT, TAN, PER, etc..

